

Sediment Yield Estimation using Garde's Model in Sonwal Watershed

Ravindra Bansod

How to cite this article:

Ravindra Bansod/Sediment Yield Estimation using Garde's Model in Sonwal Watershed/Indian Journal of Waste Management. 2021;5(1):21-24.

Abstract

The study was conducted, in Sonwal watershed of Shahada taluka, Nandurbar district, Maharashtra with an area of 9934 ha, located in 74° 53' to 74°75' N and 21°54' to 21°62' E for estimation of sediment yield using Garde's method. The observed sediment yield of the Sonwal watershed in 2002-03 was 5.88 t/ha/yr. However, it was found 10.22 t/ha/yr in 2008-09, with an increase of 4.34 t/ha/yr. The estimated sediment yield of the watershed for the year 2002-03 using Garde's equation was found to be 12.37 t/ha/year with per cent change in observed and estimated sediment yield, 110.37. The estimated sediment yield of the watershed for the year 2008-09 was found to be 14.82 t/ha/year with per cent change in observed and estimated sediment yield, 45. To reduce the rate of increase of sediment yield, the agriculture area needs to be increased by decreasing the wastes land besides, the watershed development program need to be implemented effectively to reduce the sediment yield or soil loss.

Keywords: Sonwal watershed; Garde's method and sediment yield.

Introduction

Soil erosion is a common problem in India due to mismanagement of the watershed and lack of soil and water conservation treatments. Sedimentation due to soil erosion depletes the capacity and life of soil and water conservation structures and reservoirs which leads into uneconomic and over estimation of the structures. Since part of the sediment eroded from an area can deposit in the lower reaches, the rate of erosion is usually greater than the rate at which sediment is carried downstream at any section. It may be mentioned that since landscape formation and changes in it are due to differential erosion and deposition of sediment, erosion, sediment yield and landscape formation are closely interrelated; therefore study of soil erosion and sediment yield assumes great

importance in river morphology (Garde et. al. 1987). Garde's equation/method, of which the parameters like rainfall, drainage density, and slope are more or less similar to the parameters, (R, L, S), of Universal Soil Loss Equation (USLE). The USLE does not mention the geological condition of an area however it is so important for the erosion factor calculation. In Garde's equation (eq.1), the vegetal cover factor (Fc) represents the geographical condition of the area, therefore, we use this method for estimation of sediment yield.

Materials and Methods

Study Area

The research was conducted, during 2013-15, in Sonwal watershed, of Shahada taluka, Nandurbar

Author's Affiliation: Professor, Agricultural Engineering, College of Agriculture, Pune, Maharashtra 411005, India.

Correspondence Author: Ravindra Bansod, Professor, Agricultural Engineering, College of Agriculture, Pune, Maharashtra 411005, India.

Email: rtuljapur1808@gmail.com

district, Maharashtra with an area of 9934 ha, located in 74° 53' to 74°75' N and 21°54' to 21°62' E with average elevation of 455 m above sea level. Satpura Mountain Range just 30 km from north of Shahada, the basaltic bedrock is on an average 5 metres below the ground level. The watershed is situated on Gomai tributary of Tapi River, empties in it at Changdev in Prakasha in Nandurbar district. It originates in Satpura Mountain North Maharashtra and merge into the Tapi River.

Climate

The maximum temperature of the region reaches to 48 °C and minimum to 9° C. The climate of Shahada is dry except during the south-west monsoon season and winter months December to February with an average rainfall of 552 mm.




Fig. 1: Location of study area. (Source: Provide by author).

Data used

The data required for study was as follows

- Digital imagery data: Landsat 7 for year 2002-03 and 2008-09.

- Mean annual rainfall (mm) for year 2002-03 and 2008-09.
- Monthly rainfall data (mm) for year 2002-03 and 2008-09.
- Survey of India toposheet (1: 50,000) (Toposheet No. 46 K/10).
- Observed sediment yield for year 2002-03 and 2008-09.

Garde's Equation

This equation is based on observations of 50 catchments spreading evenly all over the India. This sediment yield equation is dependent not only on catchment area, but also on other parameters like slope, drainage density, annual rainfall and vegetal cover factor. The sediment yield equation developed by (Garde et al. 1987) used by (Upadhyay et al. 2012) is as under

$$V_{SAB} = 1.182 \times 10^{-6} \times A^{1.03} \times P^{1.29} \times S^{0.08} \times D_d^{0.40} \times F_{c2.42} \quad (1)$$

Where,

V_{SAB} = Sediment yield in (Mm^3 / year),

A = Watershed area (km^2),

P = Annual precipitation (mm),

S = Average watershed slope (m/m),

D_d = Drainage density (km^{-1}) and

F_c = Vegetative cover factor.

Calculation of vegetative cover factor (F_c)

The vegetative cover factor equation developed by (Garde et al. 1987) used by (Upadhyay et al. 2012) is as under.

$$F_c = \frac{0.8 F_A + 0.6 F_G + 0.3 F_F + 0.1 F_W}{A} \quad \dots(2)$$

Where,

F_A = Area under Agriculture land (km^2),

F_G = Area under Grass land (km^2),

F_F = Area under Forest area (km^2),

F_w = Area under Waste land (km^2) and

A = Total watershed area.

Drainage Density (D_d)

The drainage density is the ratio of total channel length to the area of the watershed. A drainage map of the study area (the Survey of India toposheet at a scale of 1:50,000) was used for drainage map preparation and calculating the drainage density. The ArcGIS Software was used to draw the different order streams and calculate the length which directly gives the drainage density.

Slope map and stream slope (S)

The slope map was prepared using the ASTER DEM and using the SOI toposheet. Stream slope was calculated by dividing the total fall between the end points of the main stream by its length.

Results and Discussion

Sediment yield estimation by Garde's equation

Calculation of vegetative cover factor (Fc)

The value of Fc factor was calculated by putting values of area under forest land (km²), agriculture land (km²), grass land (km²) and waste land (km²) in equation (2). These areas were calculated using LULC map. The value of Fc for year 2002-03 was 0.638 and for year 2008-09, 0.638.

Drainage density (D_d)

The length of watershed was taken from drainage map using attribute table in ArcGIS software. As shown in Fig.1, the length of watershed basin was found to be 305.356 km. The area of the Sonwal watershed was 99.34 km². Therefore, the value of D_d was 3.073 km⁻¹.

Slope map and stream slope (S)

The length of main stream was 22.24 km and the total fall between the ends points of the main stream, 177 m. Therefore, the stream slope of the watershed was 0.00796 m/m.

Sediment yield estimation using Garde's equation

After putting all values (Fc, D_d, S, A, P) in equation (1), sediment yield for year 2002- 03 was 12.37 t/ha/yr and for year 2008-09, 14.82 t/ha/yr.

Change detection in sediment yield estimation using Garde's equation

The estimated sediment yield for the watershed for year 2002-03 using Garde's equation was found to

be 12.37 t/ha/year. The observed sediment yield for the watershed for year 2002-03 was 5.88 t/ha/yr. Per cent change in observed and estimated sediment yield was 110.37. The sediment yield in the watershed, for year 2008-09, was found to be 14.82 t/ha/yr. The observed sediment yield for year 2008-09 was 10.22 t/ha/yr. As depicted in Table 2, the sediment yield was increased from 2002-03 to 2008-09 by 2.45 t/ha/yr. Per cent change in observed and estimated sediment yield was 45 (Table 3).

Table 2: Increase in sediment yield in 2008-09 over 2002-03 of Sonwal watershed using.

Garde's equation

Year 2002-03	Year 2008-09	Increase in Sediment yield in 2008-09 over 2002-03
Sediment yield (t/ha/year)	Sediment yield (t/ha/year)	(t/ha/year)
12.37	14.82	2.45

Table 3: Comparison of observed and estimated sediment yield for year 2002-03 and 2008-09 of Sonwal watershed using Garde's equation.

Year	Observed Sediment yield (t/ha/year)	Estimated Sediment yield (t/ha/year)	Percent Change in Sediment yield (%)
2002-03	5.88	12.37	110.37
2008-09	10.22	14.82	45

Conclusions

Based on the results of the study, conclusions obtained are as follow

- The increasing trend in sediment yield was observed from 2002-03 to 2008-09.
- The rate of increase was of sediment yield was to the tune of 73.80 % from 2002-03 to 2008-09.
- The sediment yield using Garde's equation shows the per cent change 110.37 and 45 for 2002-03 and 2008-09 respectively.
- The area under cultivation need to be increased and insitu soil conservation, besides drainage line treatment should be followed for reduction of sediment yield in watershed.
- The flow though water drainage path must be restricted with a speed less than nonerosive velocity with respect to soil texture and surface roughness.

References

1. Garde, R. J. and U. C. Kothiyari. 1987. Sediment yield estimation. *J. Irrig. and Power India*, 44(3): 97-123.
2. Jain, M. K. and U. C. Kothiyari. 2000. Estimation of soil erosion and sediment yield using GIS. *Hydro. Sci. J.*, 45(5): 771-786.
3. Jain, S. K., P. Singh, A. K. Saraf and S. M. Seth. 2003. Estimation of Sediment Yield for a Rain, Snow and Glacier Fed River in the Western Himalayan Region. *Water Resources Management*, 17: 377-393.
4. Kothiyari, U. C. and S. K. Jain. 1997. Sediment yield estimation using GIS. *J. Irrig. & Drain. Engg. Div.* ASCE Hydrological Sciences-Journal-des Sciences Hydrologiques, 42(6): 833-843.
5. Suvendu Roy. 2013. Generating iso-erosion rate zones for the kunur river basin using combine methods of soil erosion estimate. *International Journal of Geology, Earth & Environmental Sciences*, 3 (2):77-89.
6. Upadhyay, R., K. A. Pandey, S. K. Upadhyay and A. Bajpai. 2012. Annual Sedimentation Yield and Sediment Characteristics of Upper Lake, Bhopal, India. *Research Journal of Chemical Sciences*, 2(2): 65-74.

