

REVIEW ARTICLE

Nano-Robotic Neurosurgery and Anesthetic Management Strategies

Kunal Kumar Sharma¹, Bharti Chauhan²

HOW TO CITE THIS ARTICLE:

Kunal Kumar Sharma, Bharti Chauhan. Nano-Robotic Neurosurgery and Anesthetic Management Strategies. Ind J Anesth Analg. 2026; 13(1): 25-32.

ABSTRACT

Background: Nano-robotic neurosurgical procedures represent a frontier in minimally invasive surgery, offering unprecedented precision in treating neurological disorders. These procedures introduce unique anesthetic challenges that require tailored approaches to ensure patient safety and procedural success.

Aim: This review explores key anesthetic considerations for nano-robotic neurosurgery, focusing on strategies to optimize patient outcomes.

Issue: Anesthetic management prioritizes stable hemodynamics and intracranial pressure (ICP) to optimize the surgical field and protect neural structures. General anesthesia using total intravenous anesthesia (TIVA), using agents like propofol and remifentanyl, is preferred for rapid titration and minimal impact on cerebral blood flow. Intraoperative neuromonitoring is employed for real-time neural function assessment, avoiding neuromuscular blockers that may interfere with signal accuracy. Protocols accommodate prolonged procedure times, patient immobility for nano-robot precision, and monitoring for potential thermal or mechanical neural irritation causing seizures or autonomic responses.

Conclusion: Nano-robotic neurosurgery demands specialized anesthetic protocols to address challenges such as stable hemodynamics, ICP control, and neuromonitoring compatibility. Effective collaboration between anesthesiologists, neurosurgeons, and nano-robotics engineers is critical to ensure patient safety and procedural success. Postoperative care emphasizes early neurological assessment and balanced pain management to support rapid recovery in this evolving field.

KEYWORDS

• Nanobots • Neurosurgery • Robotic Surgery • Anesthesia

AUTHOR'S AFFILIATION:

¹ Assistant Professor, Neuroanesthesia Cell, Indira Gandhi Medical College, Shimla, India.

² Senior Resident, Department of Neuroanesthesia, Postgraduate Institute of Medical Education and Research, Chandigarh, India.

CORRESPONDING AUTHOR:

Kunal Kumar Sharma, Assistant Professor, Neuroanesthesia Cell, Indira Gandhi Medical College, Shimla, India.

E-mail: kunaal_kumar@yahoo.com

Received: 16-10-2025

Accepted: 18-12-2025



Creative commons non-commercial CC BY-NC: This article is distributed under the terms of the creative commons attribution non-commercial 4.0 License (<http://www.creativecommons.org/licenses/by-nc/4.0/>) which permits non-commercial use, reproduction and distribution of the work without further permission provided the original work is attributed as specified on the Red Flower Publication and Open Access pages (<https://rfppl.co.in>)

INTRODUCTION

The rapid evolution of technology in the 21st century has profoundly transformed neurosurgery. From the introduction of the operating microscope to neuronavigation and intraoperative imaging, neurosurgery has consistently embraced technological innovation. Among the most transformative advances are robotic-assisted neurosurgery and intraoperative neuro-monitoring (IONM). Together, these modalities have revolutionized the precision, safety, and outcomes of neurosurgical procedures.

Robotic neurosurgery integrates artificial intelligence, computer vision, and mechanical dexterity to enhance surgical accuracy, minimize invasiveness, and improve reproducibility. Concurrently, neuro-monitoring ensures real-time assessment of neural pathway integrity, reducing the risk of iatrogenic injury.

The concept of robot-assisted surgery emerged in the 1980s with early prototypes like the PUMA 560 robot, which performed the first stereotactic brain biopsy in 1985.¹ Initially, robotic systems were limited by computing power, imaging accuracy, and lack of haptic feedback.

By the late 1990s and early 2000s, systems such as NeuroMate (Integrated Surgical Systems) and Neuromate (Renishaw) were introduced, offering precise instrument positioning for stereotactic procedures.² Later, the ROSA® robot (Zimmer Biomet)³ and Neuromaster⁴ expanded applications into deep brain stimulation (DBS), epilepsy surgery, and tumor resection.

The development of frameless stereotaxy, intraoperative MRI (iMRI), and CT-based neuronavigation paved the way for seamless integration between imaging and robotic systems. This integration allowed for automatic registration, target tracking, and dynamic correction of brain shift.

Neurosurgery has traditionally been constrained by the physical limitations of human dexterity and instrument size. Conventional microsurgical and endoscopic approaches, though refined, are limited when navigating the brain's intricate microvasculature, deep-seated lesions, or delicate ventricular systems. Recent advances in nanotechnology, material science, and robotics have enabled the conceptualization and early development

of miniaturized neuro-robots (nanorobots) designed to operate within the intravascular or intraventricular compartments of the brain.

These submillimeter-scale robotic systems represent a frontier in minimally invasive neurosurgery potentially capable of performing diagnostics, targeted drug delivery, microdissection, and real-time imaging within regions previously inaccessible through conventional techniques.

Nanorobots are synthetic, autonomous or semi-autonomous machines operating at the nanometer to micrometer scale (1–1000 μm). They are typically composed of biocompatible materials such as silicon, gold, titanium, carbon nanotubes, or biodegradable polymers and can be magnetically, chemically, acoustically, or optically actuated.⁵

The design of a neuro-nanorobot addresses several critical parameters like-(i) Biocompatibility and non-immunogenicity within cerebrospinal fluid (CSF) or blood; (ii) Navigation control within complex three-dimensional environments; (iii) Energy supply; (iv) Real-time localization and imaging capability; (v) Functional payload such as drug reservoirs, microgrippers, or imaging sensors. Brain's microenvironment, characterized by tight vascular channels (capillary diameter 3–10 μm) and high sensitivity to mechanical trauma, imposes extraordinary demands on precision, surface smoothness, and propulsion mechanisms of these devices. Table 1 addresses the potential advantages of nano-robots in neurosurgery.

Table 1: Advantages of Nano-robots with respect to key features

Feature	Advantage
Accuracy	Sub-millimetric precision for instrument placement
Reproducibility	Consistent results across surgeons and procedures
Reduced Fatigue	Robotic arms maintain steady positions for prolonged surgeries
Minimally Invasive	Smaller incisions and shorter recovery
Integration	Seamless link with imaging and neuro-monitoring systems
Safety	Real-time error correction and trajectory tracking

Current Challenges

The propulsion and navigation of nanorobots within neural structures is one of the most challenging engineering problems. Magnetically controlled nanorobots, powered by external magnetic fields, are among the

most feasible designs for neurosurgical applications. Systems like helical magnetic micro-swimmers imitate bacterial flagella and can be steered using rotating magnetic fields. Magnetic resonance imaging (MRI) scanners, or specialized electromagnetic coils, can provide both visualization and propulsion fields simultaneously. Such systems allow non-contact control, minimizing tissue heating and damage.⁶

Nanorobots can employ catalytic reactions e.g., decomposition of hydrogen peroxide or glucose oxidation to generate thrust. However, chemical propulsion in the CNS is limited by potential toxicity and the need for fuel delivery within the cerebrovascular environment.

Acoustic (ultrasound-based) actuation uses acoustic standing waves to propel or guide nanoparticles. Similarly, optical tweezers utilize focused light beams for nanoscale manipulation, though tissue penetration of light remains a limitation for deep brain applications.

Emerging designs integrate biological components such as bacterial flagella, red blood cells, or molecular motors with synthetic structures, forming biohybrid nanorobots. These leverage natural motility and adaptability for controlled movement in viscous CSF or vascular environments.

Application in Neuropathologies

The intravascular route offers a physiologically continuous and minimally invasive pathway to the brain, enabling nanorobots to traverse through arteries and capillaries for targeted intervention. The potential clinical scenarios where nanorobots will be used in neurosurgery have been summarized in table 2.

Nanorobots can be loaded with neuroprotective agents, thrombolytics, chemo-therapeutics, or gene-editing vectors (e.g., CRISPR-Cas9 complexes).⁷ Guided to precise vascular territories, they could deliver drugs directly to ischemic penumbra in acute stroke, transport chemotherapeutics across the blood-brain barrier for glioma treatment and release neurotrophic factors or genetic material for neuroregenerative therapy. The ability to bypass or transiently open the BBB under magnetic or acoustic control represents a transformative potential in neuropharmacology.^{8,9}

Miniature robotic coils or microgrippers could deploy occlusive materials inside aneurysms with unparalleled precision. Real-time control would allow dynamic adjustment

of coil placement or localized embolization in arteriovenous malformations (AVMs).

Nanorobots embedded with miniaturized sensors, such as quantum dots, fiber-optic fluorescence detectors, or nanowire electrodes, can perform localized measurement of oxygenation, pH, or neurochemical gradients, providing functional vascular imaging from within. The ventricular system and subarachnoid space provide an alternate route for nanorobot deployment, particularly for conditions where intravascular access is limited or when direct contact with CSF is desirable.

Nanorobots can be engineered to detect specific molecular markers associated with gliomas or metastases using ligand-coated sensors. Upon target recognition, they could perform micro-biopsies or signal localization through fluorescence or magnetic resonance contrast. Nanorobots equipped with magnetic nanoparticles can be guided to neoplastic sites and heated using alternating magnetic fields, inducing localized hyperthermia to destroy tumor cells while preserving surrounding tissue.

Programmable microvalve-equipped robots could regulate CSF flow dynamically, serving as intelligent shunt systems that prevent overdrainage or obstruction without the need for revision surgery. In diseases such as leptomeningeal metastasis or meningitis, nanorobots could distribute drugs uniformly through the ventricular system, overcoming the limitations of diffusion-based pharmacotherapy.

Table 2: spectrum of clinical implications with usage of nanorobots for neurosurgery

Clinical Condition	Proposed Nanorobotic Intervention	Expected Outcome
Acute ischemic stroke	Magnetically guided delivery of tissue plasminogen activator (tPA)	Rapid clot dissolution with reduced hemorrhagic risk
Glioblastoma multiforme	Targeted delivery of chemotherapeutics or hyperthermic nanoparticles	Improved tumor control, reduced systemic toxicity
Hydrocephalus	Autonomous CSF pressure-regulating nanovalves	Dynamic intracranial pressure regulation
Aneurysm	Microcoil placement via intravascular nanorobots	Precise occlusion, reduced procedural risk

Gravitas

Precise localization is critical for the safety of nanorobotic neurosurgery. Various real-time tracking systems are under exploration. MRI-guided tracking provides high-resolution visualization of magnetic nanorobots in deep brain tissue. Photoacoustic imaging combines ultrasound and optical signals for dynamic tracking. Fluorescence and bioluminescence imaging is useful for surface and experimental applications. Whereas electromagnetic tracking enables positional feedback for closed-loop robotic control.

Neuroscience is currently developing around exploratory modeling.^{10,11} Machine learning algorithms are increasingly being incorporated to predict motion trajectories, optimize navigation paths, and correct for turbulence or flow-induced deviations.

The safety of nanorobots in neural tissues is paramount. Key aspects revolve around the use of biodegradable polymers (e.g., PLGA, chitosan) that degrade into nontoxic metabolites. **Surface modification using PEGylation or protein coatings** help to reduce immune activation.

Nanorobots are designed for natural elimination via CSF resorption or macrophage uptake. External actuation systems must prevent local heating or unintended neuronal excitation, while deploying these nanobots in bloodstream. In preclinical models, magnetically guided nanoparticles have demonstrated excellent tolerability, but translation to human neurosurgery will require rigorous biocompatibility testing and long-term safety evaluation.

Magnetically driven helical nanorobots have navigated through simulated cerebral vasculature in vitro with precision up to 10 μm .¹² Hydrogel-based nanobots have demonstrated controllable expansion and drug release in response to pH changes in brain tissue models. Biohybrid microbots, powered by bacterial flagella, have achieved guided motility in cerebrospinal fluid analogues. Animal studies have shown feasibility of magnetic microbot navigation through cerebral arteries for targeted delivery of liposomal drugs. Therefore clinical translation may be achievable within the next decade, as material science and control algorithms continue to advance.

Anesthesia protocols

As the robotic neurosurgery continues to evolve, there is a dire need for simulation

protocols to be developed in neuroanesthesia as well. Therefore we enlist a set of anesthetic algorithms that dwell into this aspect. These algorithms encompasses the endovascular route, ventricular route and MRI guided route. (figures 1-5).




Figure 1: Preoperative protocol




Figure 2: Intraoperative protocol-Endovascular route




Figure 3: Intraoperative protocol: Intraventricular route




Figure 4: Protocol for Magnetic Resonance guided nano-robot procedures




Figure 5: Protocol for emergency nanorobot embolization or malfunction

Challenges and Future Directions

Despite impressive progress, several barriers still exist. There is a concern for miniaturization limits of nanobot, as further reduction in size should not cause loss of functionality of the nanobot. The omnious need for real-time communication and control still exists in order to ensure reliable, wireless feedback within brain tissue. Multimodal integration will be required in order to synchronize neuroimaging, neuro-navigation, and intraoperative monitoring systems for optimal actuation of nanobots.

Mass production under sterile and regulatory standards is still a dream far from achievement. And ethical and legal implications pose hurdles for accountability in autonomous decision-making at microscale.

Future research is focusing on swarm intelligence, where thousands of nanorobots coordinate through distributed algorithms, mimicking biological systems such as microglia or leukocytes. Such collectives could dynamically adapt to the neural microenvironment, performing simultaneous diagnostics and therapy a true theranostic revolution.

CONCLUSION

Miniaturized neuro-robots and nanorobots for intravascular and intraventricular neurosurgical interventions embody the next evolutionary step in the fusion of nanotechnology, robotics, and neuroscience. Their potential to traverse the most delicate neural pathways, deliver precision therapy, and monitor neural function in real time heralds an era of microscale, minimally invasive neurosurgery.

While many challenges remain particularly in safety validation, control precision, and regulatory oversight the trajectory of current research suggests that within the coming decades, these tiny machines may become indispensable instruments in treating cerebrovascular, neoplastic, and neurodegenerative diseases with previously unimaginable precision.

Conflict of Intrest: The authors declare that they do not have any conflict of intrest.

Funding: None

Ethics Declaration: Not required for this review article.

REFERENCES

1. Marcus HJ, Vakharia VN, Ourselin S, Duncan J, Tisdall M, Aquilina K. Robot-assisted stereotactic brain biopsy: systematic review and bibliometric analysis. *Childs Nerv Syst.* 2018;34(7):1299-1309. doi:10.1007/s00381-018-3821-y.
2. Kajita Y, Nakatsubo D, Kataoka H, Nagai T, Nakura T, Wakabayashi T. Installation of a Neuromate Robot for Stereotactic Surgery: Efforts to Conform to Japanese Specifications and an Approach for Clinical Use-Technical Notes. *Neurol Med Chir (Tokyo).* 2015;55(12):907-914. doi:10.2176/nmc.tn.2015-0043.
3. Liu L, Mariani SG, De Schlichting E, Grand S, Lefranc M, Seigneuret E, Chabardès S. Frameless ROSA® Robot-Assisted Lead Implantation for Deep Brain Stimulation: Technique and Accuracy. *Oper Neurosurg.* 2020;19(1):57-64. doi: 10.1093/ons/npz320.
4. Giridharan N, Katlowitz KA, Anand A, Gadot R, Najera RA, Shofty B, Snyder R, Larrinaga C, Prablek M, Karas PJ, Viswanathan A, Sheth SA. Robot-Assisted Deep Brain Stimulation: High Accuracy and Streamlined Workflow. *Oper Neurosurg.* 2022 Sep 1;23(3):254-260. doi: 10.1227/ons.0000000000000298.
5. Palmisciano P, Miranda R, Ling GSF, Draghic N. Nanorobotics for Neurosurgery. In: Kateb B, Heiss JD, Yu JS, Hsieh M. (eds) *The Textbook of Nanoneuroscience and Nanoneurosurgery.* Springer, Cham. 2024. doi :10.1007/978-3-030-80662-0_34.
6. Li J, Esteban-Fernández de Ávila B, Gao W, Zhang L, Wang J. Micro/Nanorobots for Biomedicine: Delivery, Surgery, Sensing, and Detoxification. *Sci Robot.* 2017;2(4):eaam6431. doi:10.1126/scirobotics.aam6431.
7. Hii ARK, Qi X, Wu Z. Advanced Strategies for CRISPR/Cas9 Delivery and Applications in Gene Editing, therapy, and cancer detection using Nanoparticles and Nanocarriers. *J. Mater. Chem. B* 2024;12:1467-1489.
8. Kong X, Gao P, Wang J, Fang Y, Hwang KC. Advances of medical nanorobots for future cancer treatments. *J Hematol Oncol.* 2023;16(1):74. doi:10.1186/s13045-023-01463-z.
9. Khan Z, Khan N, Geetha M, et al. Therapeutic applications of nanobots and nanocarriers in

- cancer treatment. *Anal Sci.* 2025;41(8):1305-1324. doi:10.1007/s44211-025-00799-5.
10. Sharma KK, Reddy KRM. Exploratory modeling of intraoperative co-oximetry data for predicting hemodynamic trends in a thalassemic patient: a pilot case. *J Neuroanaesthesiol Crit Care.* 2025;12(3):[Epub ahead of print]. doi:10.1055/s-0045-1810607.
 11. Kumar K, Gopalakrishna KN. Predictive Modeling of Intraoperative SSEP during ACOM aneurysm Clipping - A case based simulation study. In: Abstracts From the 53rd Annual Meeting of the Society for Neuroscience in Anesthesiology and Critical Care, September 12-14, 2025. *Journal of Neurosurgical Anesthesiology.* 2026;38(1):e1-e57.
 12. Zhou H, Mayorga-Martinez CC, Pané S, Zhang L, Pumera M. Magnetically Driven Micro and Nanorobots. *Chem Rev.* 2021;121(8):4999-5041. doi:10.1021/acs.chemrev.0c01234.
 13. Sharma KK, Sharma P, Surve RM. Cerebral oxygenation monitoring for early detection of subarachnoid haemorrhage in infratentorial arteriovenous malformation undergoing embolisation: A case study. *Indian J Anaesth.* 2024;68(2):206-208. doi:10.4103/ija.ija_716_23.
 14. Giergiel M. Certain problems in the development of nanorobots. *Online J Robot Autom Technol.* 2024;2(5):1-2. doi:10.33552/OJRAT.2024.02.000547.